



## MobilPlus

SAE 0W-20 Full Synthetic Motor Oil  
API SN, API SN ILSAC GF-6A, GF-5

### Product Description

**MobilPlus SAE 0W-20** is a premium full synthetic motor oil manufactured for use in modern gasoline engines which require ILSAC GF-6A, API SP, API SN Plus, or API SN performance.

This oil is formulated with synthetic base oil and a premium performance additive package which is specially formulated to protect high compression gasoline direct injection engines delivering superior oxidative stability, deposit control, low speed pre-ignition mitigation and timing chain wear protection.

### Typical Properties\*

| <u>SAE J300 Viscosity Grade</u>               | <u>0W-20</u>                      |
|---|-----------------------------------|
| <u>Appearance, Visual</u>                     | <u>Amber, Transparent, Liquid</u> |
| <u>Viscosity @ 40°C, cSt, ASTM D445</u>       | <u>44.55</u>                      |
| <u>Viscosity @ 100°C, cSt, ASTM D445</u>      | <u>8.3</u>                        |
| <u>Viscosity Index, ASTM D2270</u>            | <u>165</u>                        |
| <u>CCS Apparent Viscosity, cP, ASTM D5293</u> | <u>5,400@-35°C</u>                |
| <u>MRV Apparent Viscosity, cP, ASTM D4684</u> | <u>22,000@-40°C</u>               |
| <u>Flash Point, °C, ASTM D92</u>              | <u>210</u>                        |
| <u>Pour Point, °C, ASTM D97</u>               | <u>-47</u>                        |

\*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges

### **Exceeds Performance Requirements**

API SP with Resource Conserving, API SN Plus, API SN  
ILSAC GF-6A, GF-5  
GM dexos1™ Gen 2  
Chrysler MS6395  
Ford WSS-M2C947-A (0W-20)