



MobilPlus

SAE 10W-40 Full Synthetic Motor Oil
API SP, API SN Plus, API SN

Product Description

MobilPlus Elite SAE 10W-40 is a premium full synthetic motor oil manufactured for use in modern gasoline engines which require ILSAC GF-6A, API SP, API SN Plus, or API SN performance.

This oil is formulated with synthetic base oils and a premium performance additive package which is specially formulated to protect high compression gasoline direct injection engines delivering superior oxidative stability, deposit control, low speed pre-ignition mitigation and timing chain wear protection.

Typical Properties*

<u>SAE J300 Viscosity Grade</u>	<u>10W-40</u>
<u>Appearance, Visual</u>	<u>Amber, Transparent, Liquid</u>
<u>Viscosity @ 40°C, cSt, ASTM D445</u>	<u>68.75</u>
<u>Viscosity @ 100°C, cSt, ASTM D445</u>	<u>10.9</u>
<u>Viscosity Index, ASTM D2270</u>	<u>150</u>
<u>CCS Apparent Viscosity, cP, ASTM D5293</u>	<u>4,900@-25°C</u>
<u>MRV Apparent Viscosity, cP, ASTM D4684</u>	<u>9,000@-30°C</u>
<u>Flash Point, °C, ASTM D92</u>	<u>218</u>
<u>Pour Point, °C, ASTM D97</u>	<u>-40</u>

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges

Exceeds Performance Requirements
API SP,
API SN Plus, API SN