



## MobilPlus

SAE 5W-30 Full Synthetic Motor Oil  
API SN, API SN ILSAC GF-6A, GF-5

### Product Description

**MobilPlus SAE 5W-30** is a premium full synthetic motor oil manufactured for use in modern gasoline engines which require ILSAC GF-6A, API SP, API SN Plus, or API SN performance.

This oil is formulated with synthetic base oils and a premium performance additive package which is specially formulated to protect high compression gasoline direct injection engines delivering superior oxidative stability, deposit control, low speed pre-ignition mitigation and timing chain wear protection.

### Typical Properties\*

<u>SAE J300 Viscosity Grade</u>	<u>5W-30</u>
<u>Appearance, Visual</u>	<u>Amber, Transparent, Liquid</u>
<u>Viscosity @ 40°C, cSt, ASTM D445</u>	<u>61.25</u>
<u>Viscosity @ 100°C, cSt, ASTM D445</u>	<u>10.8</u>
<u>Viscosity Index, ASTM D2270</u>	<u>170</u>
<u>CCS Apparent Viscosity, cP, ASTM D5293</u>	<u>5,200@-30°C</u>
<u>MRV Apparent Viscosity, cP, ASTM D4684</u>	<u>18,000@-35°C</u>
<u>Flash Point, °C, ASTM D92</u>	<u>215</u>
<u>Pour Point, °C, ASTM D97</u>	<u>-42</u>

\*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges

### Exceeds Performance Requirements

API SP with Resource Conserving, API SN Plus, API SN  
ILSAC GF-6A, GF-5  
GM dexos1™ Gen 2  
Chrysler MS6395  
Ford WSS-M2C946-B1 (5W-30)