



MobilPlus

SAE 20W-50 Synthetic Blend Motor Oil
API SP

Product Description

MobilPlus Synthetic Blend Motor Oil, **SAE 20W-50** API SN Plus is formulated with a blend of conventional and synthetic base oils and a premium additive package.

These oils are formulated with group II paraffinic and synthetic base oils as well as a premium performance additive package which is specially formulated to protect high compression gasoline direct injection engines delivering superior oxidative stability, deposit control, low speed pre-ignition mitigation and timing chain wear protection.

Typical Properties*

SAE J300 Viscosity Grade	20W-50
Appearance, Visual	Amber, Transparent, Liquid
Viscosity @ 40°C, cSt, ASTM D445	148.95
Viscosity @ 100°C, cSt, ASTM D445	18.0
Viscosity Index, ASTM D2270	135
CCS Apparent Viscosity, cP, ASTM D5293	6,800@-15°C
MRV Apparent Viscosity, cP, ASTM D4684	28,000@-20°C
Flash Point, °C, ASTM D92	220
Pour Point, °C, ASTM D97	-30

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges

Exceeds Performance Requirements
API SP, API SN Plus, API SNJ