



info@mobilplus.ca 📾

2 Racine Rd, Etobicoke, ON, M9W 2Z1, Canada 😯

MobilPlus

Synthetic Blend Heavy-Duty Engine Oils SAE 20W-50 API CJ-4/SN

Product Description

MobilPlus Synthetic Blend Heavy-Duty Engine Oil, **SAE 20W-50, API CJ-4/SN** parasynthetic crankcase lubricants for use in modern diesel engines. Formulated with a blend of synthetic and conventional base oil as well as a premium quality additive package, this oil exhibits excellent detergent, dispersant, anti-wear, anti-corrosion, anti-oxidant, and anti-foaming properties.

Typical Properties*

SAE J300 Viscosity Grade	20W-50
<u>Appearance, Visual</u>	<u>Amber, Transparent, Liquid</u>
Viscosity @ 40°C, cSt, ASTM D445	<u> 160.55</u>
Viscosity @ 100°C, cSt, ASTM D445	<u> 18.5</u>
Viscosity Index, ASTM D2270	130
CCS Apparent Viscosity, cP, ASTM D	5293 6,250@-15°C
Flash Point, °C, ASTM D92	225
Pour Point, °C, ASTM D97	-30
Total Base Number, mg KOH/g, ASTN	<u>и D2896 9</u>

^{*}The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges

API SN, SM, SL, SJ, SGF