



MOBILPLUS TITANIC 2TW Robust Performance Water-cooled Ash less 2-stroke Motor oil
Quality lubricant for reliable outboard engine protection

Product Type

MOBILPLUS TIDE 2TW is top quality self-mixing oil designed with highly refined base stocks and unique ash less additive system for the superior protection of all water-cooled two-stroke gasoline outboard engines. Also applicable for use in Direct Fuel Injection (DFI) capable two-stroke recreational oils.

Performance Specifications / Standards

NMMA Recertified TC-W3

Applications

Specifically intended for the lubrication of most-modern, high-powered, water-cooled, two-stroke cycle gasoline engines used in marine outboard services, using fuel to oil ratios of 50:1, or higher, are now recommended, particularly for high-output engines.

Performance Features & Benefits

- Superior protection against piston and cylinder scuffing.
- Outstanding filterability.
- Exceptionally high resistance to heat generation and frictional power losses.
- Highly effective control over wear, rust, corrosion and ring sticking to ensure long life of moving parts.
- Trouble free ignition and protects blocking of the exhaust ports and plugs.
- Right level of detergency to keep the engine clean.
- Self-mixing capacity ensures immediate formation of a homogenous blend at all temperatures.

Typical Physical Characteristics

	NMMA	TC-W3
Density @ 15°C, kg/cu.m		0.870
Kinematic Viscosity @ 40°C, cSt		38.13
Kinematic Viscosity @ 100°C, cSt		6.4
Viscosity Index		120
Flash Point, COC, °C		110
Pour Point, °C		-35
TBN, mgm KOH/gm		8.81
Sulphated Ash, % wt		<0.001
Detergency test		Pass

Head Office:165 Dundas Street West Suite 703(Galaxy Tower) Mississauga, Ontario L5B 2N6 Canada.

+1 (647) 577-1012, +1 (437) 234-5201, www.mobilplus.ca